



G.K. Chemical Specialties Co. Inc.  
90 Barbados Blvd.  
Scarborough, Ontario M1J 1K9  
Tel: (416) 261-7182 Fax: (416) 261-5663

# Material SAFETY DATA SHEET

**PRODUCT NAME: G-475 Ammoniated Stripper and Cleaner**

<b>HEALTH HAZARD RATING:</b>	SERIOUS HAZARD – major injury likely unless prompt action is taken and medical treatment is given
<b>FLAMMABILITY HAZARD RATING:</b>	MINIMAL HAZARD – materials which are normally stable and will not burn unless heated
<b>REACTIVITY HAZARD RATING:</b>	MINIMAL HAZARD – materials, which are normally stable, even under fire conditions, and which will not react with water
<b>PERSONAL PROTECTION:</b>	Splash Goggles + Gloves + Synthetic Apron + Vapor Respirator
<b>HAZARD ALERT SIGN:</b>	HEALTH HAZARD – Extreme danger FIRE HAZARD – Will not burn REACTIVITY – Stable SPECIFIC HAZARD – Corrosive

## SECTION I – MATERIAL IDENTIFICATION AND USE / IDENTIFICATION DE LA MATIÈRE ET USAGE

### MATERIAL NAME / IDENTIFIÉRIER – NOM / IDENTIFICATION DE LA MATIÈRE

**G-475 Ammoniated Stripper and Cleaner**

MANUFACTURER'S NAME AND ADDRESS/ NOM DU FABRICANT – ADRESSE EMERGENCY PHONE NO. / N° DE TÉLÉPHONE D'URGENCE	G.K. Chemical Specialties Co. Inc. 90 Barbados Blvd. Scarborough, Ontario M1J 1K9 (416) 261-7182 / 905 427-7605
SUPPLIER'S NAME AND ADDRESS/ NOM DU FOURNISSEUR - ADRESSE EMERGENCY PHONE NO. / N° DE TELEPHONE DURGENCE	
CHEMICAL NAME / DÉNOMINATION CHIMIQUE	Not Applicable
CHEMICAL FAMILY / FAMILLE CHIMIQUE	Alkaline Solution
CHEMICAL FORMULA / FORMULE CHIMIQUE	Not Applicable
TRADE NAME AND SYNONYMS / APPELLATION COMMERCIALE ET SYNONYMES	Not Applicable
MOLECULAR WEIGHT / POIDS MOLÉCULAIRE	Not Applicable
MATERIAL USE / UTILISATION DE LA MATIÈRE	Cleaning, removing floor finish

G.K. Chemical Specialties Co. Inc. has compiled the information and recommendations contained in this Material Safety Data Sheet from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation.

G.K. Chemical Specialties Co. Inc. extends no warranty and assumes no responsibility as to the accuracy of the content or sufficiency of the information and expressly disclaims all liability for reliance thereon. This MSDS provides guidelines for the safe handling of this product. It does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required. Individuals exposed to this product should read and understand this information and be provided pertinent training prior to working with this product.

G.K. Chemical Specialties Co. Inc. assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such vendors or users assume all risks associated with the use of the material.

INGREDIENTS. This MSDS, under section of Ingredients, contains all ingredients listed under INGREDIENT DISCLOSURE LIST P.C. 1987-2719, 20/1/88 CANADA GAZETTE PART II VOL. 122, No 2 of HAZARDOUS PRODUCT ACT.

Percentage range of concentration of ingredients is expressed as percentage by weight of the total weight of the product. Ingredient List does not necessarily list all ingredients in the formulation and does not necessarily list all ingredient range of concentration, other than ingredients under the Disclosure List.

T.L.V. (units) or Threshold Limit Values refer to the limiting concentrations recommended by the Ministry of Labour. These values were adopted by the American Conference of Governmental Industrial Hygienists (A.C.G.I.H.). The figures refer to time-weighted average concentrations as P.P.M. (V/V) or mg/m<sup>3</sup> for a normal working day or at any time for some materials.

“C.A.S REG. No.” means the identification number assigned to a chemical substance by the Chemical Abstracts Service Division of the American Chemical Society.

“LC 50” means the concentration of a substance in air that when administered by means of inhalation over a specified length of time in an animal assay, is expected to cause the death of 50 per cent of a defined animal population.

“LD 50” means the single dose of a substance that, when administered by a defined route in an animal assay, is expected to cause death of 50 per cent of a defined animal population.

FLASH POINT. The minimum temperature at which a substance gives off flammable vapors which in contact with spark or flame will ignite.

**SECTION II – HAZARDOUS INGREDIENTS OF MATERIAL / INGRÉDIENTS DANGEREUX DE LA MATIÈRE**

HAZARDOUS INGREDIENTS / INGRÉDIENTS DANGEREUX	APPROXIMATE CONCENTRATION % CONCENTRATION APROXIMATIVE %	C.A.S., N.A. OR U.N. NUMBERS / NUMERO CAS NA OU CNU	LD50 {SPECIFY SPECIES & ROUTE} DL50 {PRÉCISER L'ESPECE ET LA VOIE D'ADMINISTRATION}	LC 50 {SPECIFY SPECIES & ROUTE} CL50 {PRÉCISER L'ESPECE ET LA VOIE D'ADMINISTRATION}
Caustic Soda	3-7	1310-73-2	500 mg/kgm 10% sol'n	Oral Rabbit
Ammonium Hydroxide 30%	3-7	1336-21-6	350 mg/kgm	Oral Rat
Ethylene Glycol Monobutyl Ether	1-5	111-76-2	500-5000 mg/kgm	Oral Rat
Ammonium Carbonate	0.5-1.5	Non Hazardous		
Non Ionic Surfactant	1-5	Non Hazardous		
Ester Type Surfactant	1-5	Non Hazardous		< = Less Than
Water & other Non Hazardous Ingredients	Balance	Non Hazardous		> = Greater Than

**SECTION III – PHYSICAL DATA FOR MATERIAL / CARACTÉRISTIQUES PHYSIQUES DE LA MATIÈRE**

PHYSICAL STATE / ÉTAT PHYSIQUE	Liquid
ODOUR AND APPEARANCE / ODEUR ET APPARENCE	Ammonia Clear Red Liquid Odour
ODOUR THRESHOLD (P.P.M.) / SEUIL DE L'ODEUR (PPM)	Not Available
SPECIFIC GRAVITY / DENSITE RELATIVE	1.01 ± 0.01 gm/cm <sup>3</sup>
VAPOUR PRESSURE [MM] / TENSION DE VAPEUR [MM]	< 25 at 20 °C
VAPOUR DENSITY [AIRE = 1] / DENSITE DE VAPEUR [AIR =1]	~ Water
EVAPORATION RATE / TAUX D'ÉVAPORATION	~ Water
BOILING POINT [°C] / POINT D'ÉBULLITION [°C]	100 °C
FREEZING POINT [°C] / POINT DE CONGELATION [°C]	0 °C
SOLUBILITY IN WATER [20°C] / SOLUBILITÉ DANS L'EAU [20°C]	Infinite
% VOLATILE [BY VOLUME] / % VOLATILITÉ [PAR VOLUME]	91 ± 1%
PH	Conc. 12.50 ± 0.5
COEFFICIENT OF WATER / OIL DISTRIBUTION / COEFFICIENT DE RÉPARTITION EAU / HUILE	Not Applicable

**SECTION IV – FIRE AND EXPLOSION HAZARD OF MATERIAL/RISQUES D'INCENDIE ET D'EXPLOSION DU  
MATÉRIEL**

FLAMMABILITY / INFLAMMABILITÉ __ YES / OUI __X_ NO/NON IF YES, UNDER WHICH CONDITIONS? / SI OUI, DANS QUELLES CONDISIONS?	
MEANS OF EXTINCTION / MOYENS D'EXTINCTION	Not Applicable
SPECIAL PROCEDURES / MARCHE A SUIVRE SPÉCIALE	Not Applicable
FLASHPOINT [°C] AND METHOD / POINT D'ÉCLAIR [°C] ET MÉTHODE DE DÉTERMINATION	Not Applicable
UPPER EXPLOSION LIMIT [% BY VOLUME]/ SEUIL MAXIMAL D'INFLAMMABILITÉ [% PAR VOLUME]	Not Applicable

LOWER EXPLOSION LIMIT [% BY VOLUME]/ SEUIL MINIMAL D'INFLAMMABILITÉ [% PAR VOLUME]	Not Applicable
AUTOIGNITION TEMPERATURE [°C] / TEMPÉRATURE D'AUTO-INFLAMMATION [°C]	Not Applicable
HAZARDOUS COMBUSTION PRODUCTS / PRODUITS DE COMBUSTION DANGEREUX	Small amounts of Nitrogen Oxides, Carbon Monoxide and/or Carbon Dioxide

### EXPLOSION DATA / DONNÉES SUR L'EXPLOSIBILITÉ

SENSITIVITY TO MECHANICAL IMPACT / SENSIBILITÉ AUX CHOCS	Not Applicable
SENSITIVITY TO STATIC DISCHARGE / SENSIBILITÉ AUX DÉCHARGES ÉLECTROSTATIQUES	Not Applicable

### SECTION V – REACTIVITY DATA / DONNÉES SUR LA RÉACTIVITÉ

CHEMICAL STABILITY / STABILITÉ CHIMIQUE <u> X </u> YES / OUI  NO/NON IF NO, UNDER WHICH CONDITIONS? / SI NON, DANS QUELLES CONDISIONS?	
INCOMPATIBILITY TO OTHER SUBSTANCES / INCOMPATIBILITÉ AVEC D'AUTRES SUBSTANCES <u> X </u> YES / OUI NO/NON IF SO, WHICH ONES? / SI OUI, AVEC LESQUELLES?	Acids Hypochloride bleaches product is corrosive to copper, copper alloys, galvanized surfaces
REACTIVITY AND UNDER WHAT CONDITIONS / RÉACTIVITÉ – DANS QUELLES CONDITIONS?	Acids Not dangerously reactive Hydrochloride bleaches may produce chlorine gas
HAZARDOUS DECOMPOSITION PRODUCTS / PRODUITS DE DÉCOMPOSITION DANGEREUX	Small amounts of Nitrogen Oxides, Carbon Monoxides and/or Carbon Dioxide

### SECTION VI – TOXICOLOGICAL PROPERTIES OF MATERIAL / PROPRIÉTÉS TOXICOLOGIQUES DE LA MATIÈRE

#### ROUTE OF ENTRY / VOIE D'ADMINISTRATION

X  SKIN CONTACT / CONTACT AVEC LA PEAU

X  SKIN ABSORPTION / ABSORPTION PAR LA PEAU  
No significant hazard

X  EYE CONTACT / CONTACT OCULAIRE

X  INHALATION ACUTE / INHALATION AIGUE

   INHALATION CHRONIC / INHALATION CHRONIQUE

X  INGESTION

EFFECTS OF ACUTE EXPOSURE TO MATERIAL / EFFETS DE L'EXPOSITION AIGUE A LA MATIERE	EYE CONTACT: Will cause severe irritation, may cause chemical burns. SKIN CONTACT: Brief contact may cause irritation, seen as local redness. Prolonged contact may cause chemical burns. INHALATION: Vapors or mist very irritating, to the respiratory tract INGESTION: Will cause chemicals burns of the mouth, throat, esophagus and stomach. Signs and symptoms will include pain or discomfort in the mouth, chest, and abdomen, nausea, vomiting, diarrhea, dizziness, faintness, weakness, collapse, coma.
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL / EFFETS DE L'EXPOSITION CHRONIQUE A LA MATIERE	Although no long-term human studies have been reported, there are no reported chronic effects that warrant control beyond that required for effects of acute exposure.

**MATERIAL NAME / IDENTIFIER - NOM / IDENTIFICATION DE LA MATIÈRE↓****G-475 Ammoniated Stripper and Cleaner**

LD 50 OF MATERIAL [SPECIFY SPECIES & ROUTE] / LD50 DE LA MATIÈRE [PRÉCISER L'ESPECE ET LA VOIE D'ADMINISTRATION]	4500 mg/kgm Oral Rat, ingestion of 30 ml of product or brief exposure to conc. Product may be fatal.
LC50 OF MATERIAL [SPECIFY SPECIES & ROUTE] LC50 DE LA MATIÈRE / [PRÉCISER L'ESPECE ET LA VOIE D'ADMINISTRATION]	Not Established
EXPOSURE [LIMITS] / LIMITS D'EXPOSITION	350 ppm (250 mg/m <sup>3</sup> )
IRRITANCY OF MATERIAL/PROPRIÉTÉ IRRITANTE DE LA MATIÈRE	Eyes, Skin, Lungs, Respiratory system
SENSITIZATION OF MATERIAL / SENSIBILISATION A LA MATIÈRE	Eyes, Skin, Respiratory system
SYNERGISTIC MATERIALS / MATÉRES SYNERGIQUES	None Known
CARCINOGENICITY, REPRODUCTIVE EFFECTS, TERATOGENICITY, MUTAGENICITY / CANCÉROGÉNÉCITÉ, EFFETS NOCIFS SUR LA REPRODUCTION, TÉRATOGÉNÉCITÉ, MUTAGÉNÉCITÉ	None of the ingredients contained in this product are regulated as carcinogens by OSHA

**SECTION VII – PREVENTIVES MEASURES / MESURES PRÉVENTIVES****PERSONAL PROTECTIVE EQUIPMENT / MATÉRIEL PERSONNEL DE PROTECTION**

GLOVES (SPECIFY) GANTS [PRÉCISER]	Impervious
EYE [SPECIFY] / YEUX [PRÉCISER]	Glasses, splash goggles
RESPIRATORY (SPECIFY) / APPAREIL RESPIRATOIRE (PRÉCISÉR)	Ammonium Hydroxide 100 ppm CCRS/SA/SCBA Respirator 300 ppm CCRSF 500 ppm GMS/SAF/SCBAF
OTHER (SPECIFY) / AUTRES (PRCISER)	Full protective suit is recommended whenever there is a possibility that this product could come in contact with clothing or skin.
ENGINEERING CONTYROLS [E.G. VENTILATION, ENCLOSED PROCESS, SPECIFY] / MÉCANISMES TECHNIQUES [EX. VENTILATION, OPÉRATION EN MILIEU FERMÉ, PRÉCISER]	Use with proper ventilation. Control level of ammonium hydroxide to 25 ppm ( 18mg/m <sup>3</sup> )
LEAK AND SPILL PROCEDURE / MESURES EN CAS DE FUITE OU DE DÉVERSEMENT	Small quantities may be flushed with copious amount of water; in case of large amount, contain liquid. Use phosphoric acid to cautiously neutralize. Dilute hydrochloric or muriatic acid could be used to neutralize product.
WASTE DISPOSAL / ÉLIMINATION DES RÉSIDUS	Small Amounts – sanitary sewer Large Amounts – sanitary sewer after product has been neutralized
HANDLING PROCEDURES AND EQUIPMENTS / MÉTHODES ET ÉQUIPEMENT POUR LA MANUTENTION	Avoid contact with skin and eyes. Avoid breathing ammonium hydroxide fumes.
STORAGE REQUIREMENTS / EXIGENCES D'ENTREPOSAGE	Store in closed containers, away from children. Store in a room where temperature is 0°C-40°C
SPECIAL SHIPPING INFORMATION / RENSEIGNEMENTS SPÉCIAUX POUR L'EXPÉDITION	Ammonia solutions or ammonium hydroxide with not more than 10% ammonia, Class 9.1, Pin #2672, Pkg Group III

## **SECTION VIII – FIRST AID MEASURES / PREMIERS SOINS**

---

**EYE CONTACT:** Immediately flush with lots of running water for 15 minutes, lifting the upper and lower eyelids occasionally. Get medical attention.

**SKIN CONTACT:** Immediately wash skin with lots of water. If available neutralize with diluted vinegar or lemon juice. Remove contaminated clothing and shoes; wash before reuse. Get medical attention.

**IF SWALLOWED:** Do not induce vomiting. If conscious, give lots of water or milk, then diluted vinegar, lemon juice or orange juice. Get immediate medical attention. Do not give anything by mouth to an unconscious or convulsing person.

**INHALATION:** Remove to fresh air. Give artificial respiration if not breathing. Oxygen may be given if necessary. Call a physician and/or transport to a medical facility.

---

<b>ADDITIONAL INFORMATION / RENSEIGNEMENTS SUPPLÉMENTAIRES</b>	
--	--

---

## **SECTION IX – PREPARATION DATE OF M.S.D.S. / FICHE SIGNALÉTIQUE**

---

**PREPARED BY:** Gus Kaklamanos - CHEMIST

**TELEPHONE NO.:** (416) 2617182

**DATE:** January 5, 2015

---

### **ADDITIONAL NOTES OR REFERENCES / NOTES ADDITIONNELLES OU RÉFÉRENCES:**

**NOTES:** Mild to moderate exposure to ammonium hydroxide gas can produce headache, salivation, burning of throat, perspiration, nausea, vomiting, and substernal pain. Irritation of ammonia gas in eyes and nose may be sufficiently intense to compel workers to leave area. Persons with corneal disease, and glaucoma, or chronic respiratory diseases suffer increased risk.

**WHMIS CLASSIFICATION:** CLASS E  
CLASS D, DIV. 2, SUB. A and SUB. B