



G.K. Chemical Specialties Co. Inc.  
90 Barbados Blvd.  
Scarborough, Ontario M1J 1K9  
Tel: (416) 261-7182 Fax: (416) 261-5663

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: G.K. LEMON OIL

<b>HEALTH HAZARD RATING:</b>	MODERATE HAZARD: temporary or minor injury may occur
<b>FLAMMABILITY HAZARD RATING:</b>	MODERATE HAZARD: material which must be moderately heated before ignition will occur, including flammable liquids with flash points at or above 100 °F and below 200 °F (NFPA Class II and Class IIA)
<b>REACTIVITY HAZARD RATING:</b>	MINIMAL HAZARD – materials which are normally stable, even under fire conditions, and which will not react with water.
<b>PERSONAL PROTECTION:</b>	Safety glasses + Gloves + Vapour respirator
<b>HAZARD ALERT SIGN:</b>	HEALTH HAZARD – Hazardous FIRE HAZARD – Below 200 °F REACTIVITY – Stable SPECIFIC HAZARD –

## SECTION I – MATERIAL IDENTIFICATION AND USE / IDENTIFICATION DE LA MATIÈRE ET USAGE

### MATERIAL NAME / IDENTIFIÉRIER – NOM / IDENTIFICATION DE LA MATIÈRE

#### G.K. Lemon Oil

MANUFACTURER'S NAME AND ADDRESS/ NOM DU FABRICANT – ADRESSE EMERGENCY PHONE NO. / N° DE TÉLÉPHONE D'URGENCE	G.K. Chemical Specialties Co. Inc. 90 Barbados Blvd. Scarborough, Ontario M1J 1K9 (416) 261-7182 / 905 427-7605
SUPPLIER'S NAME AND ADDRESS/ NOM DU FOURNISSEUR - ADRESSE EMERGENCY PHONE NO. / N° DE TELEPHONE DURGENCE	
CHEMICAL NAME / DÉNOMINATION CHIMIQUE	Not Applicable
CHEMICAL FAMILY / FAMILLE CHIMIQUE	Petroleum Dist.
CHEMICAL FORMULA / FORMULE CHIMIQUE	Not Applicable
TRADE NAME AND SYNONYMS / APPELLATION COMMERCIALE ET SYNONYMES	Not Applicable
MOLECULAR WEIGHT / POIDS MOLÉCULAIRE	Not Applicable
MATERIAL USE / UTILISATION DE LA MATIÈRE	Polishing, Cleaning

G.K. Chemical Specialties Co. Inc. has compiled the information and recommendations contained in this Material Safety Data Sheet from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation.

G.K. Chemical Specialties Co. Inc. extends no warranty and assumes no responsibility as to the accuracy of the content or sufficiency of the information and expressly disclaims all liability for reliance thereon. This MSDS provides guidelines for the safe handling of this product. It does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required. Individuals exposed to this product should read and understand this information and be provided pertinent training prior to working with this product.

G.K. Chemical Specialties Co. Inc. assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such vendors or users assume all risks associated with the use of the material.

INGREDIENTS. This MSDS, under section of Ingredients, contains all ingredients listed under INGREDIENT DISCLOSURE LIST P.C. 1987-2719, 20/1/88 CANADA GAZETTE PART II VOL. 122, No 2 of HAZARDOUS PRODUCT ACT.

Percentage range of concentration of ingredients is expressed as percentage by weight of the total weight of the product. Ingredient List does not necessarily list all ingredients in the formulation and does not necessarily list all ingredient range of concentration, other than ingredients under the Disclosure List.

T.L.V. (units) or Threshold Limit Values refer to the limiting concentrations recommended by the Ministry of Labour. These values were adopted by the American Conference of Governmental Industrial Hygienists (A.C.G.I.H.). The figures refer to time-weighted average concentrations as P.P.M. (V/V) or mg/m<sup>3</sup> for a normal working day or at any time for some materials.

“C.A.S REG. No.” means the identification number assigned to a chemical substance by the Chemical Abstracts Service Division of the American Chemical Society.

“LC 50” means the concentration of a substance in air that when administered by means of inhalation over a specified length of time in an animal assay, is expected to cause the death of 50 per cent of a defined animal population.

“LD 50” means the single dose of a substance that, when administered by a defined route in an animal assay, is expected to cause death of 50 per cent of a defined animal population.

FLASH POINT. The minimum temperature at which a substance gives off flammable vapors which in contact with spark or flame will ignite.

**SECTION II – HAZARDOUS INGREDIENTS OF MATERIAL / INGRÉDIENTS DANGEREUX DE LA MATIÈRE**

HAZARDOUS INGREDIENTS / INGRÉDIENTS DANGEREUX	APPROXIMATE CONCENTRATION % CONCENTRATION APROXIMATIVE %	C.A.S., N.A. OR U.N. NUMBERS / NUMERO CAS NA OU CNU	LD50 {SPECIFY SPECIES & ROUTE} DL50 {PRÉCISER L'ESPECE ET LA VOIE D'ADMINISTRATION}	LC 50 {SPECIFY SPECIES & ROUTE} CL50 {PRÉCISER L'ESPECE ET LA VOIE D'ADMINISTRATION}
Heavy Aliphatic Petroleum Distillate	30-50	64742-96-7	LD 50-Oral > 8000 ml/kgm (RAT) LC 50: >2000 mg/cv.m/4-H (RAT) LD 50 – Dermal > 4000 ml/kgm (RAT)	
Petroleum Distillate	30-50	64741-65-7	LD 50-Oral > 8000 ml/kgm (RAT) LC 50: >5900 mg/cv.m/4H (RAT) LD-50 Dermal > 4000 ml / kgm (RAT)	
White Mineral Oil	10-20	8042-47-5	Non Hazardous	
Lemon Perfume	3-7		Non Hazardous	
Other Non Hazardous ingredients	Balance			> = Greater than one < = Less than one

**SECTION III – PHYSICAL DATA FOR MATERIAL / CARACTÉRISTIQUES PHYSIQUES DE LA MATIÈRE**

PHYSICAL STATE / ÉTAT PHYSIQUE	Liquid
ODOUR AND APPEARANCE / ODEUR ET APPARENCE	Clear Yellow Oily Liquid. Lemon Odour
ODOUR THRESHOLD (P.P.M.) / SEUIL DE L'ODEUR (PPM)	Not Applicable
SPECIFIC GRAVITY / DENSITE RELATIVE	0.80 ± 0.05 gm/cm <sup>3</sup>
VAPOUR PRESSURE [MM] / TENSION DE VAPEUR [MM]	< 25
VAPOUR DENSITY [AIRE = 1] / DENSITE DE VAPEUR [AIR =1]	Heavier than Air
EVAPORATION RATE / TAUX D'ÉVAPORATION	Slower than Ether
BOILING POINT [°C] / POINT D'ÉBULLITION [°C]	178 °C – 272 °C
FREEZING POINT [°C] / POINT DE CONGELATION [°C]	< -20 °C
SOLUBILITY IN WATER [20°C] / SOLUBILITÉ DANS L'EAU [20°C]	Not Soluble
% VOLATILE [BY VOLUME] / % VOLATILITÉ [PAR VOLUME]	> 90%
PH	Not Applicable
COEFFICIENT OF WATER / OIL DISTRIBUTION / COEFFICIENT DE RÉPARTITION EAU / HUILE	Not Applicable

**SECTION IV – FIRE AND EXPLOSION HAZARD OF MATERIAL/RISQUES D'INCENDIE ET D'EXPLOSION DU  
MATÉRIEL**

FLAMMABILITY / INFLAMMABILITÉ <u>X</u> YES / OUI ___ NO/NON IF YES, UNDER WHICH CONDITIONS? / SI OUI, DANS QUELLES CONDISIONS?	Heat, Source of Ignition
MEANS OF EXTINCTION / MOYENS D'EXTINCTION	Use CO <sub>2</sub> , Foam, Dry Chemicals
SPECIAL PROCEDURES / MARCHE A SUIVRE SPÉCIALE	Water or foam may cause frothing. Use water to keep fire exposed containers cool. Handle as combustible liquid. Wear self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode when fighting fires.

FLASHPOINT [°C] AND METHOD / POINT D'ÉCLAIR [°C] ET MÉTHODE DE DÉTERMINATION	52 °C 125 °F
UPPER EXPLOSION LIMIT [% BY VOLUME]/ SEUIL MAXIMAL D'INFLAMMABILITÉ [% PAR VOLUME]	1.0
LOWER EXPLOSION LIMIT [% BY VOLUME]/ SEUIL MINIMAL D'INFLAMMABILITÉ [% PAR VOLUME]	6.0
AUTOIGNITION TEMPERATURE [°C] / TEMPÉRATURE D'AUTO-INFLAMMATION [°C]	Not Established
HAZARDOUS COMBUSTION PRODUCTS / PRODUITS DE COMBUSTION DANGEREUX	CO, CO <sub>2</sub>

### EXPLOSION DATA / DONNÉES SUR L'EXPLOSIBILITÉ

SENSITIVITY TO MECHANICAL IMPACT / SENSIBILITÉ AUX CHOCS	Not Applicable
SENSITIVITY TO STATIC DISCHARGE / SENSIBILITÉ AUX DÉCHARGES ÉLECTROSTATIQUES	Not Applicable

### SECTION V – REACTIVITY DATA / DONNÉES SUR LA RÉACTIVITÉ

CHEMICAL STABILITY / STABILITÉ CHIMIQUE <input checked="" type="checkbox"/> YES / OUI <input type="checkbox"/> NO/NON IF NO, UNDER WHICH CONDITIONS? / SI NON-, DANS QUELLES CONDISIONS?	
INCOMPATIBILITY TO OTHER SUBSTANCES / INCOMPATIBILITÉ AVEC D'AUTRES SUBSTANCES <input checked="" type="checkbox"/> YES / OUI <input type="checkbox"/> NO/NON IF SO, WHICH ONES? / SI OUI, AVEC LESQUELLES?	Avoid strong oxidizing materials Avoid sparks, open flames and any source of ignition
REACTIVITY AND UNDER WHAT CONDITIONS / RÉACTIVITÉ – DANS QUELLES CONDITIONS?	Strong oxidizing materials
HAZARDOUS DECOMPOSITION PRODUCTS / PRODUITS DE DÉCOMPOSITION DANGEREUX	CO, CO <sub>2</sub> and various hydrocarbons

### SECTION VI – TOXICOLOGICAL PROPERTIES OF MATERIAL / PROPRIÉTÉS TOXICOLOGIQUES DE LA MATIÈRE

#### ROUTE OF ENTRY / VOIE D'ADMINISTRATION

SKIN CONTACT / CONTACT AVEC LA PEAU  SKIN ABSORPTION / ABSORPTION PAR LA PEAU  
 EYE CONTACT / CONTACT OCULAIRE  INHALATION ACUTE / INHALATION AIGUE  
 INHALATION CHRONIC / INHALATION CHRONIQUE  INGESTION

EFFECTS OF ACUTE EXPOSURE TO MATERIAL / EFFETS DE L'EXPOSITION AIGUE A LA MATIERE	Moderately irritating to skin and eyes; can cause defatting dermatitis. The vapours are moderately irritating to the eyes and respiratory passages. Prolonged exposure to high vapour concentration or ingestion can cause headache, nausea, dizziness, anesthesia and central nervous system depression.
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL / EFFETS DE L'EXPOSITION CHRONIQUE A LA MATIERE	Not Applicable

**MATERIAL NAME / IDENTIFIER - NOM / IDENTIFICATION DE LA MATIÈRE↓****G.K. Lemon Oil**

LD 50 OF MATERIAL [SPECIFY SPECIES & ROUTE] / LD50 DE LA MATIÈRE [PRÉCISER L'ESPECE ET LA VOIE D'ADMINISTRATION]	Oral Rat > 8000 mg/kgm Dermal > 4000 mg/kgm
LC50 OF MATERIAL [SPECIFY SPECIES & ROUTE] LC50 DE LA MATIÈRE / [PRÉCISER L'ESPECE ET LA VOIE D'ADMINISTRATION]	> 2000 mg   cv.m   4 H (rat)
EXPOSURE [LIMITS] / LIMITS D'EXPOSITION	5 mg/kgm
IRRITANCY OF MATERIAL/PROPRIÉTÉ IRRITANTE DE LA MATIÈRE	Skin, Eyes, Respiratory tract
SENSITIZATION OF MATERIAL / SENSIBILISATION A LA MATIÈRE	Skin, Eyes
SYNERGISTIC MATERIALS / MATÉRES SYNERGIQUES	None Known
CARCINOGENICITY, REPRODUCTIVE EFFECTS, TERATOGENICITY, MUTAGENCY / CANCÉROGÉNÉCITÉ, EFFETS NOCIFS SUR LA REPRODUCTION, TÉRATOGÉNÉCITÉ, MUTAGÉNÉCITÉ	None of the ingredients contained in this product are regulated as carcinogens by OSHA.

**SECTION VII – PREVENTIVES MEASURES / MESURES PRÉVENTIVES****PERSONAL PROTECTIVE EQUIPMENT / MATÉRIEL PERSONNEL DE PROTECTION**

GLOVES (SPECIFY) GANTS [PRÉCISER]	Impervious rubber gloves.
EYE [SPECIFY] / YEUX [PRÉCISER]	Glasses, Goggles
RESPIRATORY (SPECIFY) / APPAREIL RESPIRATOIRE (PRÉCISÉR)	Approved organic canister mask or air supplied respirator. Maintain exposure limits
OTHER (SPECIFY) / AUTRES (PRCISER)	Overalls, Apron
ENGINEERING CONTROLS [E.G. VENTILATION, ENCLOSED PROCESS, SPECIFY] / MÉCANISMES TECHNIQUES [EX. VENTILATION, OPÉRATION EN MILIEU FERMÉ, PRÉCISER]	For small quantities normally used - general
LEAK AND SPILL PROCEDURE / MESURES EN CAS DE FUITE OU DE DÉVERSEMENT	Eliminate all sources of ignition. Wear adequate respiratory protection. Absorb with absorbent material. Remove to a container. Keep material away from sewers and waterways.
WASTE DISPOSAL / ÉLIMINATION DES RÉSIDUS	SMALL SPILL: Dispose of in accordance with all local and federal regulations.  LARGE SPILL: Destroy by incineration in accordance with applicable regulations.
HANDLING PROCEDURES AND EQUIPMENTS / MÉTHODES ET ÉQUIPEMENT POUR LA MANUTENTION	Handle with Care. Avoid contact with eyes and skin.
STORAGE REQUIREMENTS / EXIGENCES D'ENTREPOSAGE	Store in closed containers away from source of ignition. Keep away from children.
SPECIAL SHIPPING INFORMATION / RENSEIGNEMENTS SPÉCIAUX POUR L'EXPÉDITION	None Required

## **SECTION VIII – FIRST AID MEASURES / PREMIERS SOINS**

---

EYES CONTACT: Hold eyelids open and flush with plenty water.

SKIN CONTACT: Wash with water.

IF SWALLOWED: Induce vomiting, drink 2-3 glasses of water and see a physician.

---

<b>ADDITIONAL INFORMATION / RENSEIGNEMENTS SUPPLÉMENTAIRES</b>	
--	--

---

## **SECTION IX – PREPARATION DATE OF M.S.D.S. / FICHE SIGNALÉTIQUE**

---

**PREPARED BY:** Gus Kaklamanos - CHEMIST

**TELEPHONE NO.:** (416) 2617182

**DATE:** January 5, 2015

---

**ADDITIONAL NOTES OR REFERENCES / NOTES ADDITIONNELLES OU RÉFÉRENCES:**

WHMIS CLASSIFICATION: Class D, 2B