



G.K. Chemical Specialties Co. Inc.
90 Barbados Boulevard
Scarborough, Ontario
M1J 1K9
Phone (416) 261-7182

PRODUCT INFORMATION

G-3000 ENDURO ACRYLIC EMULSION SEALER

GENERAL: G-3000 is a thermoplastic acrylic water-based sealer for both concrete and tile floors. This system exhibits superiority in chemical resistance, oil resistance and film toughness when compared to standard emulsion sealers that have been available to the industry for many years. G-3000 is non-flammable, non-yellowing and dries within 20-40 minutes. Moreover this formulation provides outstanding balance of detergent resistance and removability, high standards of durability, scuffing and dirt pick-up. G-3000 offers high resistance to water spotting, high standards of anti-slip and high gloss.

USE: G-3000 is an ideal sealer for inter-locking bricks, terrazzo floors, ceramic tiles, concrete floors, asphalt tiles, vinyl, vinyl asbestos and linoleum. On brick and concrete walls (interior or exterior) lasts indefinitely to prevent pitting, dusting, and to stop penetration of moisture.

DIRECTIONS: Remove from flooring all trace of dirt, or other substances that might affect penetration or bonding. Rinse thoroughly and allow to dry. Apply G-3000 with a mop, lambswool applicator, soft cloth or spray. if a second coat is required , apply after initial coat is thoroughly dry.**REMOVAL:** G-3000 may be removed when desired, using an organic amine stripper and standard stripping techniques. **STORAGE AND HANDLING:** Keep in closed containers. Keep from freezing. Do not store below 32°F.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOUR AND APPEARANCE: Milky liquid-mild ammonia and polymiric odour

PH: 8.00 ± 0.6

% VOLATILE (BY VOLUME): 75.0 ± 0.5

SPECIFIC GRAVITY: 1.01 ± 0.02 gm/cm³

FREEZING POINT (°C): 0°C

COVERAGE: 1st coat 50-80 sq. meters/litre, 2nd coat 70-110 sq. meters/litre