

PRODUCT INFORMATION

G-75 SPRAY BUFF COMPOUND

GENERAL: G-75 is a dual purpose acrylic spray buff in ready-to-use form formulated to restore floor finishes to their original high gloss and enhance the cleaning process. This product is designed to bond to the existing finish, and repair worn and abraded areas of existing finish. G-75 polishes to a high gloss, removes black-heel and scuff marks and provides slip resistance. G-75 can be used with either high or low speed buffing machines to remove black heel marks, tar, ingrained dirt and surface scratches. Ready-to-use formula eliminates messy dilutions and prevents costly mistakes. G-75 is economical. One gallon covers 25-30,000 square feet. Saves time and money by avoiding stripping and multiple coat dry time.

DIRECTIONS: Dust or damp mop as required. Adjust spray nozzle for fine mist. Spray two or three sprays on an area about four feet by six feet and machine with spray buff pad (do not spray heavily as over-spray will "load" pad causing excess drag and will slow the cleaning process). Machine buff dry. After buffing is complete, dust mop floor if dust is present. Rinse spray nozzle under running water to remove residue. To obtain maximum gloss, a substantial floor finish base is required. Three coats of high quality finish are recommended. Heavily trafficked areas occasionally require additional floor finish to maintain an adequate base.

CHEMICAL AND PHYSICAL SPECIFICATIONS:

- % SOLIDS BY WEIGHT: 6.2 ± 0.2
- PH: 8.5 ± 0.5
- SPECIFIC GRAVITY: $1.01 \pm 0.01 \text{ gms/cm}^3$
- PHYSICAL APPEARANCE: Opaque liquid
- ODOUR: Polymeric-free from objectionable odour
- VISCOSITY AT 25°C : 3-10 cps (Brookfield)
- FREEZE-THAW STABILITY: 3 cycles
- STABILITY-SHELF LIFE: Stable (12) twelve months at 21°C , (1) one month at 48°C